

Product sheet

AD-844 MS adhesive

Adhesive-Adhésif AD-844 MS



Urethane based adhesive (Hybrid polymer)

■ USE

Commercial and residential

For adhering solid hardwood, exotic wood, engineered wood and bamboo. For sound reduction and vapor barrier protection to floor assemblies.

■ FEATURES

- Isocyanate-free formulation
- Virtually odorless
- Low VOC (8 g/L)
- Cleans up easily from hands and prefinished wood flooring
- Offers soundproofing properties which optimizes acoustic performance of the floor assembly

■ MECHANICAL ASSETS

- Easy to apply with excellent trowel ridge holdout
- Perfect for double-glued down standard installation
- In one single step, glue down wood and avoid vapour emissions that usually cause cupping

■ VERSATILITY

- Approved for use with all types of flooring, including short lengths of hardwood and exotic woods. Also suitable for parquet flooring, bamboo flooring, acrylic impregnated wood, laminate floor, any thickness of cork underlayment and engineered wood
- Vapor protection coating, noise reduction and adhesive in a single product and a single application
- Also suitable for standard floor installations in dry than in wet areas where humidity levels are too high and are often problematic (over 3 lbs/1000 sq.ft./24 hrs). Creating a simple and cost effective solution. No need to wait for the full cure time of the slab or recommended humidity conditions before installing wood floor
- Approved for use with ceramic tile and stone in mixed media installations using wood flooring

■ CREDIBILITY

- Meets strict wood flooring manufacturer's requirements
- Contribute to obtain LEED® credits

